

**WOOD/COAL BURNING STOVE  
SUPPLEMENTAL INSPECTION FORM**

|                |            |
|----------------|------------|
| Insured's Name | Policy No. |
|----------------|------------|

|   |  |  |   |  |
|---|--|--|---|--|
| <b>Stove/Furnace Unit</b>                     | Type   | <input type="checkbox"/> Open Hearth (No doors) <input type="checkbox"/> Pot Belly, Box or Franklin (Loose fitting doors) <input type="checkbox"/> Airtight (Tight-fitting, draft-limiting doors and seams)            |   |  |
|   | Construction   | <input type="checkbox"/> Sheet Metal <input type="checkbox"/> Cast Iron <input type="checkbox"/> Brick Lined                      Any Cracks or Broken Parts? <input type="checkbox"/> Yes <input type="checkbox"/> No |   |  |
|   | Fuel   | <input type="checkbox"/> Wood <input type="checkbox"/> Coal <input type="checkbox"/> Other (specify):  |   |  |
|   | Principal Use  | <input type="checkbox"/> Primary Heat Source (More than 50 days/yr.) <input type="checkbox"/> Supplemental Heating (Less than 50 days/yr.) <input type="checkbox"/> Cooking  |   |  |
|   | Installed By   | <input type="checkbox"/> Owner <input type="checkbox"/> Contractor <input type="checkbox"/> Month/Year of Installation   |   |  |
|   | Inspected By   | <input type="checkbox"/> Building Inspector <input type="checkbox"/> Fire Department <input type="checkbox"/> Other (specify):   |   |  |
| <b>Chimney/Chimney Connector (Stove Pipe)</b> | Installation   | Stove placed at least 36" from combustible well or furnishings, or 18" from non-combustible shield with 1" air space to combustible wall.  | Non-combustible pad or surface below stove, extends at least 18" beyond loading door and 12" beyond side and rear.  | Stove legs allow at least 4" air space below stove.  |
|   |  | <input type="checkbox"/> Yes <input type="checkbox"/> No   | <input type="checkbox"/> Yes <input type="checkbox"/> No  | <input type="checkbox"/> Yes <input type="checkbox"/> No   |
|   | Type   | <input type="checkbox"/> Masonry <input type="checkbox"/> U.L. Listed Metal Chimney  |   |  |
|   | Cleaned/Inspected  | When last cleaned (Mo./Yr.)  | Last inspected (Mo./Yr.)  | Are ashes disposed of in a fireproof container? <input type="checkbox"/> Yes <input type="checkbox"/> No |
|   | Installation   | Passes through non-combustible thimble collar or opening which is at least 12" larger in diameter than stove pipe:<br><br><input type="checkbox"/> Yes <input type="checkbox"/> No                                     | Connector to chimney under 10' in length:<br><br><input type="checkbox"/> Yes <input type="checkbox"/> No           | Galvanized steel pipe:<br><br><input type="checkbox"/> Yes <input type="checkbox"/> No                   |
|   | More than two bonds:<br><br><input type="checkbox"/> Yes <input type="checkbox"/> No | Horizontal portion rises at least 1/4" per linear ft. of pipe length so chimney connection point is higher than stove end:<br><br><input type="checkbox"/> Yes <input type="checkbox"/> No                             | Pipe sections overlap to contain creosote flowback:<br><br><input type="checkbox"/> Yes <input type="checkbox"/> No |  |
| <b>Recommendations</b>                        |  |  |   |  |

